

www.xcmg.com

TWCC150 履带起重机 TWCC150 CRAWLER CRANE

本印刷品所包含的数据，会随着产品的不断升级而改变，请以实际产品为准。
Pictures and data in this catalog will change with the update and modification of products, so please take the actual vehicle as reference.



911120



TWCC150 履带起重机

TWCC150
CRAWLER
CRANE

徐工集团工程机械股份有限公司建设机械分公司

XCMG CONSTRUCTION MACHINERY CO., LTD. BUILDING MACHINERY CO.


技术性能参数/整机基本尺寸 Technical Specification/Overall Dimension

主要零部件 Main Parts

目录 CONTENTS




主要零部件 Main Parts	1
详细介绍 Detailed Introduction	4
组装 Assembly	6
主臂臂节组合/主臂工况 Boom Combinations/Boom Working Condition	7
主臂作业范围 Boom Working Area	8
主臂工况载荷表 Boom Working Condition and Lifting Load Chart	9
固定副臂工况 Fixed Jib Working Condition	10
固定副臂作业范围 Fixed Jib Working Area	11
固定副臂工况载荷表 Fixed Jib Working Condition and Lifting Load Chart	12

项目 Items	单位 Unit	数值 Data
最大额定起重能力 Max. rated lifting capacity	t	150
基本型主臂 Basic boom	t	15
固定副臂 Fixed jib	t	840
主臂长度 Boom length	m	19~82
主臂变幅角度 Boom elevating angle	(°)	-3~82
固定副臂长度 Fixed jib length	m	12~30
起升机构最大升降速度(空载、第五层) Winch mechanism max. single line speed (no load, at 5th layer)	m/min	120
变幅机构最大升降速度(空载、第五层) Elevating mechanism max. single line speed (no load, at 5th layer)	m/min	30
最大回转速度 Max. slewing speed	r/min	1.5
最大行走速度 Max. traveling speed	km/h	1.1
爬坡度 Grade ability	%	30
平均接地比压 Average ground pressure	Mpa	0.093
发动机功率 Engine power	kW	220
整机质量(主吊钩、19米臂) Mass of the vehicle as a whole (including main hook block and 19m boom)	t	150
运输状态单件最大质量 Max. mass of single unit in travel configuration	t	53
运输状态单件(转台)最大尺寸(长×宽×高) Max. dimension of single unit in travel configuration (L×W×H)	m	11.5x3.3x3.3




	主机 Main Unit × 1 长 L 11450mm 宽 W 3300mm 高 H 3260mm 重量 Weight 53000kg
	150t吊钩 Capacity Hook Block × 1 长 L 2248mm 宽 W 1040mm 高 H 850mm 重量 Weight 2400kg
	100t吊钩 Capacity Hook Block × 1 长 L 1870mm 宽 W 700mm 高 H 650mm 重量 Weight 1530kg
	65t吊钩 Capacity Hook Block × 1 长 L 1770mm 宽 W 770mm 高 H 440mm 重量 Weight 990kg
	30t吊钩 Capacity Hook Block × 1 长 L 1550mm 宽 W 770mm 高 H 350mm 重量 Weight 710kg
	上车1号配重 Superstructure Weight Counterbalance I × 1 长 L 4400mm 宽 W 1510mm 高 H 948mm 重量 Weight 13000kg
	上车2号配重 Superstructure Weight Counterbalance II × 1 长 L 4400mm 宽 W 1510mm 高 H 530mm 重量 Weight 10000kg

主要零部件 Main Parts

	上车3号配重 Superstructure Weight counterbalance III ×2 长 L 4400mm 宽 W 1510mm 高 H 530mm 重量 Weight 10500kg
	上车4号配重 Superstructure Weight counterbalance IV ×1 长 L 4400mm 宽 W 1510mm 高 H 530mm 重量 Weight 8000kg
	履带架 Track Frame ×2 长 L 8454mm 宽 W 1100mm 高 H 1338mm 重量 Weight 21500kg
	主臂底节臂 Boom Butt ×1 长 L 9240mm 宽 W 2130mm 高 H 2100mm 重量 Weight 3290kg
	主臂3米节 Boom Insert ×2 长 L 3130mm 宽 W 2130mm 高 H 1930mm 重量 Weight 523kg
	主臂6米节 Boom Insert ×1 长 L 6130mm 宽 W 2130mm 高 H 1930mm 重量 Weight 973kg
	主臂9米节 Boom Insert ×3 长 L 9130mm 宽 W 2130mm 高 H 1930mm 重量 Weight 1272kg

主要零部件 Main Parts

	主臂12米节 Boom Insert ×2 长 L 12130mm 宽 W 2130mm 高 H 1930mm 重量 Weight 1524kg
	主臂顶节臂 Boom Top ×1 长 L 10490mm 宽 W 2130mm 高 H 2050mm 重量 Weight 2470kg
	主臂臂端单滑轮 Boom Single Top ×1 长 L 1033mm 宽 W 1160mm 高 H 970mm 重量 Weight 163kg
	固定副臂底节臂 Fixed Jib Butt ×1 长 L 6230mm 宽 W 1082mm 高 H 890mm 重量 Weight 384kg
	固定副臂中间节 Fixed Jib Insert ×3 长 L 6100mm 宽 W 1082mm 高 H 890mm 重量 Weight 275kg
	固定副臂顶节臂 Fixed Jib Top ×1 长 L 6430mm 宽 W 1082mm 高 H 890mm 重量 Weight 373kg

说 明 Notes

- 以上零部件插图形状为示意图，标注尺寸为设计值，不包括包装。
The above parts dimension is only for illustration, the dimension shown is design value, and does not include the package
- 重量为设计值，由于制造误差，可能稍有不同。
The weight is design value, may have slight difference due to error in manufacture

详细介绍 Detailed Introduction

上 车

发动机

采用沃尔沃 TAD941VE 系列：水冷、增压、电喷发动机，额定功率 220kW，额定转速为 2000rpm，最大输出扭矩 1401N·m，符合符合欧洲工程机械第二阶段排放标准。

控制系统

智能化计算机集成式可编程控制系统，是产品的关键核心技术，采用 PLC 可编程控制器，并与常规电气相结合，完成系统的逻辑控制与电气控制功能，实现起重机的自动控制，大大提高起重机的作业安全性，可靠性和作业效率。本机的操作可以通过电脑的大屏幕显示出来，很方便的实现了人机对话。

液压系统

采用液控比例阀，升开回路，交叉敏感型泵系统，液压系统组成：超高压路、变幅系统、回转系统、行走系统、辅助安全系统。
特点：采用开式系统，主泵为交叉敏感型泵，液压先导控制变量，具有功率限制功能，可以满足多个执行元件作业要求，回转精度高，起制动、换向平稳，可以满足频繁换向、换向操作。

起升机构

主、副起升机构相同，单独驱动，设卷筒减速机：开式罩壳制链器，防止形成藏式减速机。主、副起升机构与转台采用销轴连接，便于拆装、驱动马达、平衡轴、起升钢丝绳均为德国进口，最大速度可达 120m/min，具有优良的调速性能，起升机构还具有换油方便、噪音低、高效率、长寿命等特点。

变幅机构

主臂变幅为一个双联卷筒独立驱动，主臂变幅机构采用内藏式减速机（力士乐公司），片式制动制动器，卷筒设有棘轮锁止装置，以策机械制动，安全可靠，主臂变幅机构与转台采用销轴连接，便于拆装、驱动马达、平衡轴均为德国进口。

回转机构

回转机构布置在转台内圈前面，与回转支承内配合，液压油缸、具有自由回转功能，行星齿轮减速机，可承载高、行星制动器，工作可靠，维护方便。

回转支承

采用徐州罗特艾德公司的三排滚柱式回转支承，承载稳定可靠。

上车配重

配重布置在转台的后面，由上至下分布为

1号配重：13t 共1块；
2号配重：10t 共1块；
3号配重：10.5t 共2块；
4号配重：8t 共1块；

Crane Superstructure

Engine

It is a VOLVO original 6-cylinder, water cooled, supercharging and intercooled electric spray TAD941VE engine with rated output power 220kW, rated rotation speed 2000 rpm and maximum output torque 1401N·m. Emission is in compliance with European Construction Machinery Stage II.

Control System

Intelligent computer integrated programmable control system is the key technology of the crane PLC programmable controller is used in combination with conventional electrics, to realize the logic and the electronic proportional control functions of the system, and to improve safety, reliability and efficiency of the crane operation. Crane operation can be shown by a larger computer display, which is convenient for man-machine interaction.

Hydraulic System

It takes electronic proportional control, close/open type circuit, constant power and variable displacement pump system. Hydraulic system, winch system, elevating system, slewing system, tower jib backstop, propel system, auxiliary assembly system. Features: winch, elevating and propel systems use open type system, main pump is a crossed sensing variable displacement pump, wherein, variable displacement is controlled by hydraulic pilot, with a function of power limit. Main pump may satisfy the requirement of multiple actuator movement. Slewing system has the advantages of quick response, accurate control, stable starting, braking and direction changing, and can satisfy the operation of frequent direction changing and fine motion.

Winch System

Main/auxiliary winch has the same model, is driven independently and of supplied by confluence of two pumps. It takes disc type constant closed brake and built-in speed reducer from Rexroth, main/auxiliary winch and turntable are connected by pin shaft, easy for assembly. Its maximum speed is 120m/min, with good fine speed performance. Winch system also features easy oil replacement, low noise, high efficiency and long service life.

Elevating System

Boom elevating system has built-in speed reducer (Rexroth), and disc type constant closed brake, winch drum has a ratchet locking device to realize safely and reliably mechanical braking. Boom elevating system connects with turntable by pin shaft, which makes assembly easily. Drive motor, balance valve and elevating wire rope are all imported from Germany.

Slewing System

Slewing system is arranged at the front of the turntable and internal meshed with the slewing ring. It has the function of hydraulic buffering and free slewing. Controllable constant-closed disc brake of the planetary reducer works reliably and is easy for maintenance.

Slewing Bearing

It takes 6-row roller type slewing bearing made by Xuzhou Rothe Erde with stable and reliable quality.

Superstructure Counterweight

Counterweights locate on the rear of turntable, from the top down they are Superstructure Counterweight I 13t 1slab Superstructure Counterweight II 10t 1 slab Superstructure Counterweight III 10.5t 2 slab Superstructure Counterweight IV 8t 1 slab

详细介绍 Detailed Introduction

操纵室

操纵室采用钢制框体结构，正面配置有整体式夹胶玻璃，其余玻璃均为钢化玻璃，装有可调式座椅，按人机工程学布置的全套操纵仪器和控制装置。配置冷暖空调、音响、灭火器装置、闭路电视系统等，美观舒适。

转台

转台采用箱型与单腿板梁式的结构，该结构整体稳定性好，转台变幅系主车架的关键承载结构件，转台通过回转支承与车架进行连接。操纵室、起升机构、变幅机构、发动机、平衡轴、销轴、臂架及配重等分别与转台在不同部位进行连接。

下 车

下车包括车架、履带架、行走机构，车架和履带架采用插入式连接，履带架的拆装可利用履带运输车进行吊装。

车架

车架采用高强度板，箱形结构，中间设置横隔板，加强箱形刚度，结构简单，承载能力强，刚性好。

履带架

包括履带架和驱动一带，履带架采用箱形结构，与车架连接部位局部加强，中间设置横隔板，两个履带架对称布置，具有宽度为 1m 的履带架。

行走机构

履带行走驱动采用德国进口的行星式行星齿轮减速机，液压释放行走制动器，每个减速机由德国进口的轴向柱塞变量马达驱动，可同步操作，也可单独操作，以实现直行和转弯。

行走速度

在履带马达可以实现无级变速，最高速度 1.1 公里/小时，行走时，设备运行平稳，可实现在地行走。

作业装置

主臂臂架包括主臂和固定副臂，结构形式为中间等截面，两端变截面的四弦杆桁架梁结构，主臂杆件采用进口高强度管材，副臂采用国产管材，提高了臂架转弯的刚度。

主臂

主臂为中间等截面，两端变截面的全桁架梁式结构，钢管焊接，臂架顶部与桁架桁架加强，以利于传递载荷，主臂配置液压平衡制动器，主臂长度为 19~82m。

出底：底节臂 9m，中间节臂 3m×2，中间节臂 6m×1，中间节臂 6m×3，中间节臂 12m×2，总臂臂 10m。

Operator's Cabin

Operator's cabin is steel frame structure. Its front windshield is provided with overall sandwich glass, other glass is all hardened glass. Equipped with adjustable seat, a set of ergonomic designed instruments and control devices, air-conditioner, CD player, fire extinguisher, monitor and so on, the cabin is comfortable.

Turntable

Turntable is a mixed structure of box type and single web plate, with good overall stability. Turntable is a key structural part linking crane superstructure with and crane carrier for load bearing. It connects with the carrier through slewing bearing. Operator's cabin, winch system, elevating system, engine, gantry, mast, boom and counterweight etc. respectively connect with the turntable at different positions.

Crane Carrier

Crane carrier comprises car-body, track frame, and propel unit. Car-body and track frame take insert-type connection. The assembly and disassembly of the track frame can be aided by another crane.

Car-body

Car body uses high strength H-shape structure. With cross panel installed in the middle to strengthen its stiffness against torsion, it features simple structure, high loading capacity and well rigidity.

Track Frame

Track frame consists of track beam, drive sprocket, idler wheel, upper roller, lower roller and track. Crawler beam takes box-shape structure. Its connection position with frame is strengthened partially, and cross panel is installed in the middle of it. Two track frames are symmetrically arranged, with track blocks of 1m width.

Propel Unit

Propel unit has built-in planetary gear reducer and hydraulic release service brake imported from Germany. Each reducer is driven by German imported axial piston variable displacement motor, can be operated synchronously or independently to realize straight travel and turning around.

Traveling Speed

Variable displacement motor can realize infinite variable speed whose maximum value is 1.1 km/h.

Lifting Operation Parts

Lifting boom comprises main boom and fixed jib, both of which are lattice structure of four tubular chords with intermediate equal section and two end variable section, wherein, main boom chord use imported high strength tube and web rod use domestic high quality tube.

Boom

Main boom is the lattice structure of intermediate equal section and two end variable section and welded by steel tubes. Boom top and boom foot are reinforced by steel plates for load transfer and boom is equipped with single top boom length 19m, boom insert 3m×2, boom insert 6m×1, boom insert 9m×3, boom insert 12m×2, boom top 10m.

详细介绍 Detailed Introduction

固定副臂

固定副臂为中间等截面、两端变截面的桁架桥式结构，桁架臂根、臂尖顶部与地面桁架板加强，以利于传递载荷。
固定副臂可在主臂长46~73米范围内进行，其作业长度为12~30m，含10°及30°两种安装角度。
固定副臂通过支架及固定副臂销，与主臂及主臂连为一体，随着主臂变幅结构的起与落率达到固定副臂的工作幅度。
组别：底节臂6m，中间节臂6m*3，顶节臂6m。

桅杆

桅杆结构为箱形双柱结构，该结构整体稳定性好，装有桅杆提升油缸，用油缸顶桅杆及入字架。在自拆装时，可拆成桅杆座，用于拆装臂架。

人字架

人字架是重要结构件之一，前段采用箱形双柱结构，后段采用可折叠式结构。

吊钩

标配：150t吊钩、100t吊钩、65t吊钩、30t吊钩

安全装置

安全装置包括力矩限制器、转台回转限位装置、起重量防后翻装置、起升高度限位装置、防撞仪、水平仪、液位系统的溢流阀、平衡阀、双向液锁阀、回转警告等。

力矩限制器

检测功能：力矩限制器能自动检测出起重臂的角度、起重载荷。
显示功能：实时显示当前实际载荷、工作半径、起重臂角度。
警告功能：如果检测到实际载荷超过额定载荷，起重臂超过极限角度，力矩限制器发出报警并限制臂的转动。

主、副提升过卷装置

当主、副卷扬机升到一定高度时，仪表板上的过卷保护装置灯亮，同时力矩限制器停止起升动作。

主、副提升过放装置

过放保护功能由安装在卷筒内部接引钢丝绳检测卷筒上的钢丝绳下三卷时触发，仪表板上指示灯亮，同时力矩限制器自动停止起升动作。

棘爪锁止装置

该功能用于固定支腿卷扬，起重臂降落的时候必须打开该装置，否则不能降落，用于保护臂架在作业时安全停放。

Fixed Jib

Fixed jib is the lattice structure of intermediate equal section and two end variable section and welded by steel tubes. Jib top and jib foot are reinforced by steel plates for load transfer.
Fixed jib can be operated within the range of boom length 46~73m and lifting operation length is 12~30m with two offset angle of 10° and 30°. Fixed jib is connected with boom by supporting strut and front and rear guy cables, and reach its working radius with raising and lowering of boom elevating system.
Construction: jib butt 6m, jib insert 6m*3, jib top 6m.

Mast

It takes box-type structure of twin tubular chord with a good stability and equipped with oil cylinder for lifting and lowering mast and gantry. When self assembly and disassembly, it can be used as mast crane to mount and demount boom.

Gantry

Gantry is one of the important structural parts, its front part is box-type structure of twin tubular chord and the rear part is folded pendant.

Hook Block

Standard configuration: 150t capacity hook block, 100t capacity hook block, 65t capacity hook block and 30t capacity hook block.

Safety Devices

Safety devices comprise: load moment limiter, turntable lock pin, boom backstop, height limiter, anemometer, level gauge, hydraulic overflow valve, balance valve, two-way hydraulic lock, stowing warning, etc.

Load Moment Limiter

Detection function: automatically detect boom angle and lifting load.
Display function: real time display current actual load, working radius and boom angle.
Warning function: automatically send out warning signal and stop crane operation when detecting actual load exceeding rated load and boom out of limit angle.

Main/Auxiliary Winch Over-Wind Protection Device

When main/auxiliary winch hoists up to a certain lifting height, an over-wind warning lamp on instrument panel lights on. At the same time, load moment limiter stops crane operation.

Main/Auxiliary Winch Over-Release Protection Device

When access switch in winch drum detects only three turns of wire rope left on the drum, an over-release warning lamp on instrument panel lights on. At the same time, load moment limiter stops crane operation.

Winch Ratchet Locking Device

Winch drum has a ratchet locking device which must be turned on when lowering boom. Otherwise boom cannot be lowered. The device is used to stow the boom for safety.

详细介绍 Detailed Introduction

起重臂角度限制

当起重臂角度在60°时，起重臂将停止起升，由力矩限制器和行程开关联锁控制，当起重臂角度小于30°时停止起重臂落，由力矩限制器控制。

监控系统（选配）

由两个摄像头和一个显示器组成，分别监控主、副卷扬和变幅卷扬。

声光报警器

在臂架起重量做回转动作的时候灯闪烁并发出声音报警。

力限器三色报警灯

当三色灯颜色组成，负载在90%以下时“绿灯”亮，表示起重臂在安全区域运行，负载在90%-100%的时候“黄灯”亮，表示起重臂在已接近额定载荷范围，负载在100%-105%以上时“红灯”和“黄灯”同时亮，表示起重臂已超载。在危险区域，控制系统自动切断起重机的运行。

照明灯

设置在转台前方、臂架上和司机室内，用于夜间工作提供照明。

示高灯

安装在臂架顶部，作为高度显示。

风速仪

实时检测当前风速，传递到驾驶室的风速器上，提醒司机操作的安全。

Boom Angle Limit

When boom angle is more than 60°, load moment limiter and hoist limit switch stop boom rising. When boom angle is less than 30°, load moment limiter stops boom lowering.

Monitoring System

It consists of two cameras and one monitor to monitor the main, auxiliary and derrick winches respectively.

Audio/Video Warning

When crawler crane is slewing, the device blinks and warns.

LMI Tricolor Warning Lamp

The lamp comprises 3 colors, when crane loading is below 90% of total rated lifting load, "Green Lamp" lights on to indicate that crane is running in safety, when crane loading is in 90%~100% of total rated lifting load, "Yellow Lamp" lights on to indicate that crane is close to total rated lifting load, when crane loading is above 100%~105% of total rated lifting load, both "Red Lamp" and "Yellow Lamp" lights on to indicate that crane is overloaded. In dangerous area, control system can automatically cut off crane movement to dangerous direction.

Illumination Lamp


There are illumination lamps at the front of turntable, on boom and inside operator's cabin for night operation.

Height Mark Lamp


Boom tip has a height mark lamp for high level operation warning.

Anemometer

Anemometer at boom head can detect current wind speed and send wind signal to a monitor in operator's cabin to alert operator for safety.




臂长 Boom length (m)	底节臂 Boom butt 9m	3m	中间节臂 Boom insert			顶节臂 Boom top 10m
19	1	-	-	-	-	1
22	1	1	-	-	-	1
25	1	-	1	-	-	1
28	1	-	-	1	-	1
31	1	1	-	1	-	1
34	1	-	1	1	-	1
37	1	1	1	1	-	1
40	1	1	-	2	-	1
43	1	-	1	2	-	1
46	1	-	-	3	-	1
49	1	1	-	3	-	1
52	1	-	1	3	-	1
55	1	1	1	3	-	1
58	1	2	1	3	-	1
61	1	1	-	3	1	1
64	1	2	-	3	1	1
67	1	2	-	2	2	1
70	1	1	1	2	2	1
73	1	2	1	2	2	1
76	1	2	-	3	2	1
79	1	1	1	3	2	1
82	1	2	1	3	2	1



主臂作业范围 Boom Working Area

主臂工况载荷表 Boom Working Condition and Lifting Load Chart





半径 Radius (m)	臂长 Boom length (m)											
	19	22	25	28	31	34	37	40	43	46	49	52
5	150.0											
6	140.0	130.0	117.0									
7	110.0	110.0	110.0	100.0	90.0							
8	90.0	95.5	94.0	91.0	88.0	85.5	84.0					
9	82.5	80.7	80.5	79.0	77.0	75.8	74.0	72.0	69.4			
10	71.0	69.2	68.1	66.0	64.0	62.6	61.0	64.4	64.2	61.0	59.0	
12	55.0	54.3	54.6	54.4	54.2	54.0	53.0	52.0	51.0	49.6	49.0	48.0
14	45.0	44.6	44.4	44.2	44.0	43.8	43.6	43.3	42.9	42.0	41.0	40.0
16	38.0	38.8	37.0	36.8	36.6	36.4	36.2	36.0	35.6	35.6	34.0	33.8
18		32.6	32.0	31.6	31.4	31.2	31.0	30.8	30.6	30.4	30.2	30.0
20			28.0	27.9	27.7	27.5	27.3	27.1	26.9	26.8	26.6	26.0
22				25.4	25.2	25.0	24.8	24.2	24.0	23.8	23.6	23.4
24					22.0	21.8	21.6	21.4	21.2	21.0	20.8	20.6
26						19.8	19.6	19.4	19.2	19.0	18.2	18.0
28							17.9	17.6	17.4	17.2	16.8	16.6
30								16.0	15.6	15.4	15.0	15.7
32									14.8	14.6	14.4	14.0
34										13.9	13.6	13.2
36											12.0	11.5
38												10.6
40												9.8
42												9.4
44												8.8

半径 Radius (m)	臂长 Boom length (m)											
	55	58	61	64	67	70	75	76	79	82		
12	47.6	42.2										
14	39.0	38.8	38.6	38.0	35.0	30.0						
16	33.6	33.4	33.2	33.0	30.0	28.0	26.9	25.0	21.5	20.1		
18	29.8	29.6	29.2	28.8	28.0	27.2	26.2	24.2	21.4	19.5		
20	25.7	25.5	25.3	25.0	24.8	24.3	23.7	23.2	20.6	18.8		
22	23.2	23.0	22.0	21.8	21.5	21.3	20.9	20.4	19.0	18.1		
24	20.4	20.0	19.5	19.3	19.1	19.0	18.5	18.1	17.0	16.6		
26	17.7	17.6	17.4	17.1	16.9	16.8	16.6	16.2	15.7	15.2		
28	16.4	16.2	16.0	15.8	15.5	15.0	15.0	14.6	14.1	13.7		
30	15.5	15.3	15.0	14.0	13.6	13.4	13.2	13.2	12.8	12.4		
32	13.6	13.3	13.0	12.6	12.2	12.0	12.0	12.0	11.7	11.2		
34	13.0	12.6	12.0	11.6	11.1	11.0	11.0	11.0	10.7	10.3		
36	11.2	11.0	10.8	10.5	10.2	10.0	10.0	10.0	9.8	9.4		
38	10.1	9.9	9.6	9.4	9.2	9.1	9.0	9.0	9.0	8.8		
40	9.6	9.4	8.9	8.7	8.6	8.5	8.5	8.4	8.3	8.0		
42	8.8	8.6	8.2	8.0	7.9	7.7	7.7	7.7	7.6	7.4		
44	8.0	7.7	7.4	7.3	7.3	7.1	7.1	7.1	6.9	6.8		
46	7.4	7.2	7.0	6.9	6.9	6.7	6.6	6.6	6.2	6.1		
48		6.6	6.6	6.4	6.4	6.4	6.2	6.0	5.8	5.4		
50		6.5	6.2	6.0	5.9	5.9	5.6	5.3	5.0	4.9		
52			6.0	5.5	5.4	5.3	5.0	4.7	4.5	4.3		
54				5.3	5.0	4.8	4.6	4.3	4.0	3.8		
56					4.5	4.4	4.1	3.8	3.5	3.4		
58						4.1	3.8	3.4	3.1	2.9		
60							3.6	3.2	2.7	2.5		
62								3.3	2.6	2.4		

固定副臂臂节组合/副臂工况 Fixed Jib Combinations/Jib Working Condition

固定副臂作业范围 Fixed Jib Working range



固定副臂工况载荷表

Fixed Jib Working Condition and Lifting Load Chart

主臂长度 Boom length (m)		主臂46米 Boom length 46m							
副臂长度 Jib length (m)		副臂安装角 Jib offset angle (°)							
半径 Radius (m)									
		12	16	24	30	30	10	30	
		10	30	10	30	10	30	10	30
14		15.0							
15		15.0							
16		15.0	13.0	12.0					
20		15.0	13.0	12.0		8.0			
22		15.0	13.0	12.0		8.0	8.0	4.0	
24		15.0	13.0	12.0		8.0	8.0	4.0	
25		15.0	13.0	12.0		8.0	7.8	6.0	4.0
26		15.0	12.6	12.0		8.0	7.6	6.0	4.0
30		15.0	12.2	12.0		8.0	7.4	6.0	3.0
32		14.8	11.8	11.5		8.0	7.3	6.0	3.0
34		13.0	11.5	10.9		8.0	7.1	6.0	3.0
35		12.0	11.2	10.5		7.8	6.9	5.8	3.0
38		11.0	10.8	10.3		7.6	6.7	5.7	3.0
40		10.4	10.2	10.0		7.4	6.5	5.5	3.0

主臂长度 Boom length (m)		主臂49米 Boom length 49m							
副臂长度 Jib length (m)		副臂安装角 Jib offset angle (°)							
半径 Radius (m)									
		12	16	24	30	30	10	30	
		10	30	10	30	10	30	10	30
14		15.0							
15		15.0							
16		15.0	13.0	12.0					
20		15.0	13.0	12.0			8.0		
22		15.0	13.0	12.0			8.0	4.0	
24		15.0	13.0	12.0		8.0	8.0	4.0	
25		15.0	13.0	12.0		8.0	8.0	4.0	
26		15.0	13.0	12.0		8.0	7.8	6.0	4.0
30		14.9	12.8	12.0		8.0	7.6	6.0	3.0
32		13.8	12.6	12.0		8.0	7.4	6.0	3.0
34		12.8	12.0	12.0		8.0	7.2	6.0	3.0
36		11.8	11.5	11.8		8.0	7.0	5.9	3.0
38		10.5	10.6	10.6		7.8	6.8	5.8	3.0
40		9.8	9.8	9.8		7.6	6.6	5.6	3.0
42		9.0	9.0	9.0		7.4	6.4	5.4	3.0

固定副臂工况载荷表

Fixed Jib Working Condition and Lifting Load Chart

主臂长度 Boom length (m)		主臂52米 Boom length 52m							
副臂长度 Jib length (m)		副臂安装角 Jib offset angle (°)							
半径 Radius (m)									
		12	16	24	30	30	10	30	
		10	30	10	30	10	30	10	30
16		15.0							
18		15.0		12.0					
20		15.0	13.0	12.0			8.0		
22		15.0	13.0	12.0			8.0	4.0	
24		15.0	13.0	12.0		8.0	8.0	4.0	
26		15.0	13.0	12.0		8.0	8.0	4.0	
28		15.0	13.0	12.0		8.0	7.8	6.0	4.0
30		14.7	12.8	12.0		8.0	7.6	6.0	4.0
32		13.8	12.6	12.0		8.0	7.4	6.0	3.0
34		12.3	12.3	12.0		8.0	7.2	6.0	3.0
36		11.5	11.5	11.2		8.0	7.0	6.0	3.0
38		10.3	10.3	10.3		7.8	6.8	5.8	3.0
40		9.6	9.6	9.6		7.6	6.6	5.7	3.0
42		8.8	8.8	8.8		7.4	6.4	5.5	3.0
44		8.2	8.2	8.2		7.2	6.2	5.4	3.0
46		7.6	7.6	7.6		7.0	6.0	5.2	2.8

主臂长度 Boom length (m)		主臂52米 Boom length 52m							
副臂长度 Jib length (m)		副臂安装角 Jib offset angle (°)							
半径 Radius (m)									
		12	16	24	30	30	10	30	
		10	30	10	30	10	30	10	30
16		15.0							
18		15.0		12.0					
20		15.0	13.0	12.0					
22		15.0	13.0	12.0			8.0	4.0	
24		15.0	13.0	12.0		8.0	8.0	4.0	
26		15.0	13.0	12.0		8.0	8.0	4.0	
28		15.0	13.0	12.0		8.0	8.0	6.0	4.0
30		14.4	13.0	12.0		8.0	7.8	6.0	4.0
32		13.2	12.2	12.0		8.0	7.6	6.0	3.0
34		11.8	11.8	11.8		8.0	7.4	6.0	3.0
36		11.0	11.0	11.0		7.8	7.2	6.0	3.0
38		10.2	10.2	10.2		7.6	7.0	5.9	3.0
40		9.3	9.3	9.3		7.4	6.8	5.7	3.0
42		8.6	8.6	8.6		7.0	6.6	5.6	2.9
44		7.9	7.9	7.9		6.7	6.5	5.5	2.9
46		7.4	7.4	7.4		6.4	6.3	5.3	2.8
48		6.8	6.8	6.8		6.2	6.1	5.2	2.8

固定副臂工况载荷表
Fixed Jib Working Condition and Lifting Load Chart

固定副臂工况载荷表
Fixed Jib Working Condition and Lifting Load Chart

主臂长度 Boom length (m)		主臂58米 Boom length 58m									
塔臂长度 Jib length (m)	幅度 Radius (m)	副臂安装角 Jib offset angle (°)									
		12		16		24		30			
		10	30	10	30	10	30	10	30	10	30
16	15.0										
18	15.0										
20	15.0		13.0	12.0							
22	15.0		13.0	12.0		8.0					
24	15.0		13.0	12.0	8.0	8.0				4.0	
26	15.0		13.0	12.0	8.0	8.0				4.0	
28	15.0		13.0	12.0	8.0	8.0	6.0		4.0		
30	14.3		13.0	12.0	8.0	8.0	6.0	4.0			
32	12.9		12.8	12.0	8.0	7.8	6.0	4.0		3.0	
34	11.8		11.8	11.8	8.0	7.6	6.0	4.0		3.0	
36	10.8		10.8	10.8	8.0	7.4	6.0	4.0		3.0	
38	9.8		9.8	9.8	8.0	7.2	6.0	4.0		3.0	
40	9.0		9.0	9.0	8.0	6.8	5.9	4.0		3.0	
42	8.3		8.3	8.3	7.7	6.7	5.7	3.9		3.0	
44	7.7		7.7	7.7	7.5	6.6	5.6	3.8		2.9	
46	7.2		7.2	7.2	7.2	6.4	5.4	3.6		2.9	
48	6.5		6.5	6.5	6.5	6.2	5.2	3.4		2.8	
50	6.2		6.2	6.2	6.2	6.0	5.0	3.2		2.8	

主臂长度 Boom length (m)		主臂58米 Boom length 58m									
塔臂长度 Jib length (m)	幅度 Radius (m)	副臂安装角 Jib offset angle (°)									
		12		16		24		30			
		10	30	10	30	10	30	10	30	10	30
18	15.0										
20	15.0		13.0	12.0							
22	15.0		13.0	12.0		8.0					
24	15.0		13.0	12.0		8.0		8.0		4.0	
26	15.0		13.0	12.0	8.0	8.0				4.0	
28	15.0		13.0	12.0	8.0	8.0				4.0	
30	14.7		13.0	12.0	8.0	8.0	6.0			4.0	
32	13.2		13.0	12.0	8.0	7.8	6.0			4.0	3.0
34	12.0		12.0	12.0	8.0	7.6	6.0			4.0	3.0
36	11.0		11.0	11.0	8.0	7.5	6.0			4.0	3.0
38	10.1		10.1	10.1	8.0	7.3	6.0			4.0	3.0
40	9.3		9.3	9.3	8.0	7.1	5.9			4.0	3.0
42	8.5		8.5	8.5	8.0	6.9	5.8			3.9	3.0
44	7.9		7.9	7.9	7.9	6.7	5.7			3.8	2.9
46	7.3		7.3	7.3	7.3	6.6	5.6			3.7	2.9
48	6.7		6.7	6.7	6.7	6.4	5.4			3.5	2.9
50	6.2		6.2	6.2	6.2	6.2	5.3			3.4	2.8
52	5.8		5.8	5.8	5.8	5.8	5.2			3.3	2.8
54	5.4		5.4	5.4	5.4	5.4	5.1			3.2	2.7

固定副臂工况载荷表
Fixed Jib Working Condition and Lifting Load Chart

固定副臂工况载荷表
Fixed Jib Working Condition and Lifting Load Chart

主臂长度 Boom length (m)		主臂64米 Boom length 64m									
吊臂长度 Jib length (m)		12		16		24		30			
幅度 Radius (m)		副臂安装角 Jib offset angle (°)									
		10	30	10	30	10	30	10	30	10	30
18	15.0										
20	15.0			12.0							
22	15.0		13.0	12.0		8.0					
24	15.0		13.0	12.0		8.0			4.0		
26	15.0		13.0	12.0	8.0	8.0			4.0		
28	15.0		13.0	12.0	8.0	8.0			4.0		
30	14.4		13.0	12.0	8.0	8.0	6.0		4.0		
32	13.1		13.0	12.0	8.0	8.0	6.0	4.0			
34	12.0		12.0	12.0	8.0	7.8	6.0	4.0		3.0	
36	10.7		10.7	10.7	8.0	7.6	6.0	4.0		3.0	
38	9.8		9.8	9.8	8.0	7.4	6.0	4.0		3.0	
40	9.0		9.0	9.0	8.0	7.2	6.0	4.0		3.0	
42	8.2		8.2	8.2	8.0	7.0	5.9	4.0		3.0	
44	7.6		7.6	7.6	7.6	6.8	5.7	3.9		3.0	
46	7.0		7.0	7.0	7.0	6.6	5.6	3.8		3.0	
48	6.4		6.4	6.4	6.4	6.4	5.4	3.7		2.9	
50	5.9		5.9	5.9	5.9	5.9	5.3	3.6		2.9	
52	5.4		5.4	5.4	5.4	5.4	5.1	3.5		2.8	
54	5.0		5.0	5.0	5.0	5.0	5.0	3.4		2.8	
56	4.5		4.5	4.5	4.5	4.5	4.5	3.2		2.7	

主臂长度 Boom length (m)		主臂67米 Boom length 67m									
吊臂长度 Jib length (m)		12		16		24		30			
幅度 Radius (m)		副臂安装角 Jib offset angle (°)									
		10	30	10	30	10	30	10	30	10	30
18	15.0										
20	15.0			12.0							
22	15.0		13.0	12.0							
24	15.0		13.0	12.0		8.0			4.0		
26	15.0		13.0	12.0	8.0	8.0			4.0		
28	15.0		13.0	12.0	8.0	8.0			4.0		
30	14.3		13.0	12.0	8.0	8.0	6.0		4.0		
32	13.0		13.0	12.0	8.0	8.0	6.0	4.0			
34	11.8		11.8	11.8	8.0	7.8	6.0	4.0		3.0	
36	10.7		10.7	10.7	8.0	7.6	6.0	4.0		3.0	
38	9.8		9.8	9.8	8.0	7.4	6.0	4.0		3.0	
40	9.0		9.0	9.0	8.0	7.2	6.0	4.0		3.0	
42	8.2		8.2	8.2	8.0	7.0	5.9	4.0		3.0	
44	7.6		7.6	7.6	7.6	6.8	5.7	3.9		3.0	
46	7.0		7.0	7.0	7.0	6.6	5.6	3.8		3.0	
48	6.4		6.4	6.4	6.4	6.4	5.4	3.7		3.0	
50	5.9		5.9	5.9	5.9	5.9	5.3	3.6		2.9	
52	5.4		5.4	5.4	5.4	5.4	5.1	3.5		2.8	
54	4.9		4.9	4.9	4.9	4.9	4.8	3.4		2.8	
56	4.3		4.3	4.3	4.3	4.3	4.3	3.2		2.7	
58	4.0		4.0	4.0	4.0	4.0	4.0	3.0		2.6	

主臂长度 Boom length (m)		主臂70米 Boom length 70m							
吊臂长度 Jib length (m)		12		18		24		30	
幅度 Radius (m)		副臂安装角 Jib offset angle (°)							
		10	30	10	30	10	30	10	30
18	15.0								
20	15.0			12.0					
22	15.0		13.0	12.0					
24	15.0		13.0	12.0		8.0			
26	15.0		13.0	12.0	8.0	8.0		4.0	
28	15.0		13.0	12.0	8.0	8.0		4.0	
30	14.3		13.0	12.0	8.0	8.0	6.0	4.0	
32	12.9		12.0	12.0	8.0	8.0	6.0	4.0	
34	11.7		11.7	11.7	8.0	7.8	6.0	4.0	3.0
36	10.7		10.7	10.7	8.0	7.6	6.0	4.0	3.0
38	9.8		9.8	9.8	8.0	7.5	6.0	4.0	3.0
40	9.0		9.0	9.0	8.0	7.4	6.0	4.0	3.0
42	8.2		8.2	8.2	8.0	7.2	6.0	4.0	3.0
44	7.5		7.5	7.5	7.5	7.1	5.8	4.0	3.0
46	7.0		7.0	7.0	7.0	7.0	5.6	3.9	3.0
48	6.4		6.4	6.4	6.4	6.4	5.4	3.8	3.0
50	5.9		5.9	5.9	5.9	5.9	5.2	3.7	2.9
52	5.3		5.3	5.3	5.3	5.3	5.0	3.6	2.8
54	4.8		4.8	4.8	4.8	4.8	4.8	3.4	2.8
56	4.3		4.3	4.3	4.3	4.3	4.3	3.3	2.7
58	3.9		3.9	3.9	3.9	3.9	3.9	3.2	2.7
60	3.6		3.6	3.6	3.6	3.6	3.6	3.1	2.6
62	3.2		3.2	3.2	3.2	3.2	3.2	3.0	2.6

固定副臂工况载荷表

Fixed Jib Working Condition and Lifting Load Chart

主臂长度 Boom length (m)						
主臂73米 Boom length 73m						
塔臂长度 Jib length (m)						
12 18 24						
幅度 Radius (m)	副臂安装角 Jib offset angle (°)					
	10	30	10	30	10	30
18	15.0					
20	15.0					
22	15.0	13.0	12.0			
24	15.0	12.7	12.0		8.0	
26	15.0	12.4	12.0		8.0	
28	15.0	12.1	12.0	8.0	8.0	
30	14.0	11.8	12.0	8.0	8.0	
32	12.6	11.6	12.0	8.0	8.0	6.0
34	11.4	11.3	11.4	8.0	8.0	6.0
36	10.4	10.4	10.4	8.0	7.8	6.0
38	9.5	9.5	9.5	8.0	7.7	6.0
40	8.6	8.6	8.6	8.0	7.5	6.0
42	7.9	7.9	7.9	7.9	7.4	6.0
44	7.2	7.2	7.2	7.2	7.2	5.8
46	6.5	6.5	6.5	6.5	6.5	5.6
48	6.0	6.0	6.0	6.0	6.0	5.3
50	5.5	5.5	5.5	5.5	5.5	5.1
52	4.8	4.8	4.8	4.8	4.8	4.8
54	4.3	4.3	4.3	4.3	4.3	4.3
56	4.0	4.0	4.0	4.0	4.0	4.0
58	3.6	3.6	3.6	3.6	3.6	3.6
60	3.2	3.2	3.2	3.2	3.2	3.2
62	2.8	2.8	2.8	2.8	2.8	2.8

载荷表说明：

- 表中额定起重量，指在给定的臂架长度、工作幅度条件下，重物自由悬挂，在坚实、平坦地面作业所能保证的最大起重量。作业者须视各种不良条件（如地面松软或不平、风力、侧面负荷、摆动作用、多台起重机合力起吊）限制或降低起重机的起重量；
- 表中额定起重量包括吊钩、钢丝绳、和其它所有吊具的重量；
- 表中没有列出额定值的空白区，不允许将起重机用于该区所对应的起重作业；
- 表中起重量为带上车全配重的起重量；
- 使用主臂可以配置臂端单滑轮机构，臂端单滑轮机构的起重量为性能表中相应的额定起重量减去臂端单滑轮机构、30t吊钩和吊具的重量；
- 臂端单滑轮机构的最大起重量（包括吊钩、吊具和起升钢丝绳）不准超过10t，性能表中的额定起重量小于10t时按性能表起吊。

Notes on Lifting Load Chart:

- The total rated lifting loads shown in above tables are the max. lifting capacity based on the conditions that crane set up on firm and level ground with given boom length, radius and load, crane operator shall limit or reduce lifting loads according to variable working conditions (soft or uneven ground, wind, side load, slewing action, lifting with one more cranes).
- The total rated lifting loads include the weight of hook block, wire rope and other slings.
- The blank area in above tables means crane operation is not allowed in these areas.
- The total rated lifting loads are the lifting capacity for crane with superstructure counterweight.
- Boom can be equipped with a single top, whose lifting load is the total rated lifting loads in above table decrease the weight of single sheave, 30t capacity hook block and slings.
- The max. rated lifting load for single top can't exceed 10t (include the weight of hook block, slings and hoist wire rope), if rated lifting load in above tables is less than 10t, load lifting should be in accordance with the table.